



C7 Corvette Seat Skins (SED-C7-110-0X)

“Congratulations on your purchase of our C7 Corvette Seat Skins! You've made a wise investment indeed. These quality leatherette skins will give you years of good looks while protecting your seats and the value of your C7.” - Dave

Installation Instructions

Difficulty/Skill Level: Some steps may be physically challenging.
Tools/Materials: Small amount of masking tape; plastic trim tool (optional)
Revised: Jan. 4, 2019

- Please read all instruction steps before starting.
- Installation is completely reversible. No permanent modifications are made to your car.
- Although professional installation is recommended, these instructions will guide you through the process of installing your skins.
- Prior to installing the skins, make sure all pieces are present. There should be two bottom skins and two back skins. Also included is a flat plastic 'fitting stick'.
- If you have a question give us a call at (858) 939-9506.

Please read this important Disclaimer Notice:

Our C7 Corvette Seat Skins have been designed to be easy to install, have good quality, and cause no damage to your car. They have been thoroughly tested with C7 Corvettes. In the unlikely event of the C7 Corvette Seat Skins causing damage to your car we limit our liability to the price paid for the C7 Corvette Seat Skins. All other costs are assumed by the car owner. By installing, attempting to install, or using, the C7 Corvette Seat Skins you are demonstrating that you clearly understand and agree to this disclaimer. If you do not agree with this disclaimer, please let us know and we will provide Return Material Authorization (RMA) to you to facilitate a refund.

Step 1: Set A Bottom Skin In Position

- ◆ Put the seat all the way forward and raise up as high as possible.
- ◆ Lay a bottom skin over the seat. See photo for correct position. [Photo](#) [Photo](#)

Step 2: Prepare Velcro Straps

- ◆ Slide the Velcro straps that are at the back of the skin rearward between the seat back and seat bottom. Guide the straps to each side of the debris flap. The debris flap is located at the rear of the seat between the seat bottom and seat back. The straps should exit the debris flap at each side. [Photo](#) [Photo](#) [Photo](#)
[Photo](#) [Photo](#)
- ◆ Continue installation of skin by pushing skin between seat back and seat base.

Step 3: Tuck Interior Edge

- ◆ Put the seat all the way down and all the way rearward.
- ◆ Tuck interior edge of skin into place between seat and center tunnel. This may seem difficult to do but the tight fit will ensure the skin will remain solidly in place. [Photo](#) [Photo](#) [Photo](#) [Photo](#) [Photo](#)
- ◆ Note: There may be a strap attached which is not used at this time.

Step 4: Attach Back And Front Velcro Straps Together

- ◆ Put seat up and forward
- ◆ Attach a rear Velcro strap to the white fitting stick using masking tape. [Photo](#) [Photo](#) [Photo](#)
- ◆ Slide stick under the seat keeping the stick and strap as close as possible to the carpet to avoid getting tangled in the seat. [Photo](#) [Photo](#)
- ◆ Bring rear strap forward and pull tight. Pull front strap rearward to make tight. Attach front and rear Velcro straps together. [Photo](#) [Photo](#) [Photo](#) [Photo](#) [Photo](#)
- ◆ Repeat for other strap.

Step 5: Tuck Exterior Edge

- ◆ Tuck two pouches on outside of skin between the seat material and the plastic molding.
- ◆ Work the skin material under the plastic trim.
[Photo](#) [Photo](#) [Photo](#) [Photo](#) [Photo](#) [Photo](#)

Step 6: Bottom Skin Finish

- ◆ Adjust and tighten any straps as needed.
- ◆ Repeat steps 1-6 for other seat.
[Photo](#)

Step 7: Set A Back Skin In Position

- ◆ Select a back skin that corresponds to the seat back. The skin will have cutouts for the airbag housing and the seat belt guide.
- ◆ Put the seat all the way forward and raise up as high as possible. Tilt the seat back forward.
- ◆ Push the skin center hole flaps to the front of the skin. [Photo](#)
- ◆ Slide the skin over the seat back and give the skin its initial fit. Ensure the airbag cutout is fitted around the airbag housing. Ensure the seat belt guide opening is aligned with the seat belt guide. [Photo](#) [Photo](#)
[Photo](#) [Photo](#)
- ◆ There are three Velcro straps. The shortest one is near the airbag opening. This one is used to secure the rear of the skin. The other two are used to connect the side panels together. [Photo](#) [Photo](#)
- ◆ Slide the two long Nylon straps rearward between the seat back and seat bottom. Guide the straps to each side of the debris flap. [Photo](#) [Photo](#)
- ◆ Put seat all the way rearward and down. Tilt seat back to rear.
- ◆ Tuck skin between seat back and bottom, trying to get as much material as possible inserted between the back and the bottom, and between the seat and carpet. [Photo](#)

Step 8 Attach Nylon Skin Straps Together

- ◆ Put seat up and forward. [Photo](#)
- ◆ Attach a bottom Nylon strap to the white fitting stick using masking tape. [Photo](#)
- ◆ Slide stick under seat toward the front keeping the stick and strap as close as possible to the carpet to avoid getting tangled in the seat.
- ◆ Bring strap forward and pull tight. Attach strap to buckle at front of the bottom skin. [Photo](#) [Photo](#)
[Photo](#) [Photo](#)
- ◆ Repeat for other Nylon strap.

Step 9 Attach Velcro Skin Straps

- ◆ Put seat up and forward.
- ◆ Connect the two bottom Velcro straps together over the rear surface of the seat back. This will secure the sides of the skin. [Photo](#) [Photo](#) [Photo](#)
- ◆ Attach the airbag Velcro strap to the inside surface of the skin. This is best done by holding the strap against the back of the seat and pushing the skin against the strap. This holds the rear of the skin in position. [Photo](#) [Photo](#) [Photo](#)

Step 10 Attach The Center Hole Skin Flaps

- ◆ Put seat up and forward.
- ◆ Push the center hole flaps rearward completely through the hole. [Photo](#)
- ◆ Locate the flap with the bottom Velcro strip. Tuck the flap downward between the skin and seat back. Press the skin against the Velcro. [Photo](#) [Photo](#)
- ◆ Locate the flap with the top Velcro strip. Tuck the flap upward between the skin and seat back. Press the skin against the Velcro. [Photo](#) [Photo](#)
- ◆ Locate the small side flaps with the Velcro strips. Tuck the flaps between the skin and seat back. Press the skin against the Velcro. [Photo](#) [Photo](#)

Step 11 Align The Skin To The Airbag Housing And Seat Belt Guide

- ◆ Check the skin opening to the airbag housing. If not well aligned, adjust the Velcro strap as needed. [Photo](#) [Photo](#) [Photo](#)
- ◆ Check the skin opening to the seat belt guide. Tuck the front edge of the skin under the seat belt guide. [Photo](#) [Photo](#)
- ◆ Reinsert seat belt into guide. If desired, clip on your Sandyecco Designs' Seat Belt Stay. [Photo](#) [Photo](#) [Photo](#)
- ◆ Repeat steps 7-11 for the other seat.